

## Closing handle - UZ

	Reference documents:	PN-EN 61386
	Characteristics:	Lockable handle, combustible
	Application:	Fastening system for electrical system pipes of the RL and RS rigid type, but they also may be used as the corrugated pipes fastening system. Mainly used in pre-wall installations
	Material:	PP
	Scope of temperatures: (transport, installation, exploitation)	-5°C ÷ 90°C
	Colour:	White, grey (RAL 7012)
	Sizes [mm]:	13; 16; 18; 20; 22; 25; 28; 32; 37; 40; 47; 50
	NOTES:	Possibility of preparing a handle in a different colour on request



Size [mm]	White		Gray		Item / pack
	symbol	index	symbol	index	
13	UZ 13	10180	UZ 13 SZ	10188	100
16	UZ 16	10181	UZ 16 SZ	10189	100
18	UZ 18	10182	UZ 18 SZ	10190	100
20	UZ 20	10183	UZ 20 SZ	10191	100
22	UZ 22	10184	UZ 22 SZ	10192	100
25	UZ 25	10221	UZ 25 SZ	10224	100
28	UZ 28	10185	UZ 28 SZ	10193	100
32	UZ 32	10501	UZ 32 SZ	10504	100
37	UZ 37	10186	UZ 37 SZ	10194	100
40	UZ 40	10502*	UZ 40 SZ	10505*	100
47	UZ 47	10187	UZ 47 SZ	10195	100
50	UZ 50	10503*	UZ 50 SZ	10506*	100

\*product available on request