












Rigid wiring halogen-free pipe 750N - RSHF

	Reference documents:	PN-EN 61386-21
	Characteristics:	<ul style="list-style-type: none"> Rigid, flame – retardant, self-extinguishing, halogen-free pipe (fulfils requirements regarding the amount of toxic chemical compounds released during combustion) Fire reaction class: PN-EN 13501-1:2019-02: C-s3, d0
	Application:	Distribution and protection of electric wires in wall installations, flush-mounted installations, plaster walls, wooden surfaces. Recommended in places with a special degree of fire protection and in places with stricter requirements for toxic chemicals (halogen-free product).
	Material:	PP modified
	Compressive strength:	750N
	Scope of temperatures:	-5°C ÷ 90°C
	Colour:	Gray
	Ø External diameter [mm]:	16; 20; 22; 28; 37; 47
	Length of bars [m]:	3

 The manufacturer's recommendations regarding the product's installation temperature are available in the warranty card.



Ø D [mm]	L: 3m		<div></div> <div>Item / pack</div>
	Gray		
	Symbol	<div></div> index	
16	RSHF 16	10760*	20
20	RSHF 20	10761*	20
22	RSHF 22	10762*	20
28	RSHF 28	10763*	20
37	RSHF 37	10764*	10
47	RSHF 47	10765*	10

* product available on request at the minimum production requirement

