











Wiring trunking - KK

	Reference documents:	PN-EN 50085
	Characteristics:	<ul style="list-style-type: none"> • Wiring trunking, flammability class V-0, self-extinguishing • With perforated bottom • Trunking lid is covered by protective foil • Fire reaction class: PN-EN 13501-1:2019-02: B-s2, d0 • Characterised by increased durability and constancy of colour even in conditions of continuous exposure to UV radiation
	Application:	Protection of electrical wires in wall mounted installations against mechanical damage and moisture.
	Material:	PVC
	Scope of temperatures:	-15°C ÷ 60°C
	Colour:	White
	Size [mm]:	16x10; 17x15; 20x11; 20x18; 25x15; 32x15; 32x30; 40x25; 40x40; 50x18:2; 60x40; 60x60; 90x40; 90x60; 130x60
	Length of bars [m]	2

 The manufacturer's recommendations regarding the product's installation temperature are available in the warranty card.



Symbol	W x H [mm]	 index	 Number of pieces in the package
KK 16X10-40	16 x 10	10257	40
KK 17X15-40	17 x 15	10258	40
KK 20X11-40	20 x 11	10259	40
KK 20X18-40	20 x 18	10260	40
KK 25X15-30	25 x 15	10261	30
KK 32X15-30	32 x 15	10263	30
KK 32X30-28	32 x 30	10264	28
KK 40X25-24	40 x 25	10265	24
KK 40X40-20	40 x 40	10268	20
KK 50X18:2-30	50 x 18	10269	30
KK 60X40-15*	60 x 40	10270	15
KK 60X60-12*	60 x 60	10331	12
KK 90X40-10*	90 x 40	10332	10
KK 90X60-8*	90 x 60	10333	8
KK 130x60-4*	130 x 60	10262	4

* possibility to order a separator