










Compensation halogen-free connector - ZCLFHF

	Reference documents:	PN-EN 61386-25
	Characteristics:	<ul style="list-style-type: none"> • Compensation connector, flexible, flame retardant, self-extinguishing, halogen-free (fulfils requirements regarding the amount of toxic chemical compounds released during combustion) • Fire reaction class: PN-EN 13501-1:2019-02: C-s3, d0
	Application:	Fixing system for rigid halogen-free pipes in wall installations, flush-mounted installations and plaster walls.
	Material:	PP modified
	Scope of temperatures:	-5°C ÷ 90°C
	Colour:	Gray
	Size [mm]:	16; 18; 20; 22; 25; 28; 32; 37; 47

 The manufacturer's recommendations regarding the product's installation temperature are available in the warranty card.



Size [mm]	Gray		Number of pieces in the package
	Symbol	 index	
16	ZCLFHF 16	10866	100
18	ZCLFHF 18	11024	100
20	ZCLFHF 20	10867	100
22	ZCLFHF 22	10868	100
25	ZCLFHF 25	11663	100
28	ZCLFHF 28	10869	100
32	ZCLFHF 32	11664	50
37	ZCLFHF 37	10870	50
47	ZCLFHF 47	10871*	50

* product available on request at the minimum production requirement